






PB-3600

www.posiflex.com

Specification	PB-3600
Processor	VIA Nano 1.6 GHz / 1M cache CPU
System Memory	DDR3 1066 MHz, SO-DIMM x 1, max 4 GB
Storage Device	2.5" SATA HDD or SSD kit (Optional)
Power Supply	12V DC power adaptor, 60W
Audio	Buzzer
OS support	Win 7 / Windows XP Pro / POSReady / Win CE 6.0 / DOS / Linux
Color	Ivory white or black
Connectivity	
LAN Port	10 / 100 / 1000 Mb
Parallel Port	1
Serial Port	DB9 x 4, with 5V / 12V support on COM1 / COM2 / COM3 /COM4
PS/2 Keyboard	Yes
PS/2 Mouse	Yes
UPS Port	Yes, battery (Optional)
Standard USB Port	6 (5 on the I/O plate, 1 for internal use) (Optional 2 Powered USB, 1 X 12V & 1 X 24V)
VGA Port	D-SUB 15 pins, with 12V power for Posiflex LCD monitor
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	279 x 243 x 114
Weight (N. W. in kg)	2.24
Environment	
Operation Condition	0°C ~ +40°C, 20%RH - 90%RH (Equipped with HDD) 0°C ~ +50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
SSD	8 GB minimum
2nd HDD	Yes
WiFi	802.11 b / g / n, USB interface
PCI Riser Card	Half length PCI riser card
UPS Battery	2300 mAh / 12V
PB-310	2nd VGA port
PU-430	Powered USB board, 24V x 1 port, 12V x 1 port, upgraded adaptor to 150W
LM-2110 / LM-2210	10.4" TFT LCD, 800 x 600 resolution
LM-7112 / TM-7112	12" TFT active matrix LCD panel (TM-7112 is touch panel)
KP-210	36-key side mount programmable keypad with keylock and optional MSR, smart card reader (Upgraded kit with LM-7112 / TM-7112)
PD-307 / PD-307U	2 x 20 LCD, default 200 mm pole
PD-2601 / PD-2601U	2 x 20 VFD, default 200 mm pole
PD-7321	160 x 32 dots graphic LCD, default pole
PD-76X1	240 x 64 dots graphic LCD, default 200 mm pole
Certifications	<div>FCCE</div> <div></div> <div></div> <div></div> <div>ORACLE</div>

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2012 PB36Q1C1

\*\* The product information and specifications are subject to change without prior notice.

POSIFLEX

Your Success is Our Vision

Posiflex Technology, Inc.

Headquarters

No.6, Wuquan Rd., Wugu Dist., New Taipei City

248, Taiwan (R.O.C.)

Tel: +886 2 2299-1599    Fax: +886 2 2299-1819

sales@posiflex.com.tw    www.posiflex.com

Authorized Distributor / Reseller

POSIFLEX

Your Success is Our Vision



PB-3600

Valued Compact POS System



www.posiflex.com

## PB-3600

Posiflex reveals the PB-3600 as a valued compact POS System.

The PB-3600 comes with affordable performance in a small-sized POS box. It accommodates powered USB ports for applicable peripherals making deployment easier. The rear cable cover protects the I/O connections and makes the appearance look neat. And the built-in UPS function is embedded on main board developed by Posiflex for better stability of power backup than others. It's free to match Posiflex 8" – 17" LCD or touch LCD, and also supports versatile peripheral options such as MSR, customer pole display, programmable keypad, and son on to meet numerous applications.

The PB-3600 features small box to combine different type monitors for space-limited checkout. counter.checkout counter.



### Key Features

- Equipped with VIA Nano 1.6 GHz and DDR3
- HDD or SSD (Optional) storage device
- UPS (Embedded on main board developed by Posiflex) support to avoid sudden loss of power
- 2 powered USB ports (One 12V & one 24V) for peripherals without adaptors (Optional)
- Rear cable cover for safety and neat outlook



Rear cable cover for safety and neat outlook

